

The Art of Music Reproduction



3510 Pre-Amplifier

Outputs

Output Level :	1.9V for rated input (gain +18dB full volume)
Maximum Output :	7.7V RMS @ 1kHz
Frequency Response :	20Hz - 20kHz \pm 0.25dB
Total Harmonic Distortion :	<0.005%, @ 1kHz, ref rated output
Signal to Noise Ratio :	>100dB, A weighted

Inputs

Input Impedance :	18K Ohms minimum
Input Sensitivity :	250mV

General

Mains Supply :	110/120V or 220/240V, 50/60Hz (factory set)
Fuse :	T5AL for 110/120V units T2.5AL for 220/240V units
Power Consumption :	<25W
Dimensions (HxWxD) :	90mm x 440mm x 300mm
Net Weight :	7kg
Gross Weight :	9kg

Features

- Large custom made toroidal power transformer and smoothing capacitors for power supply
- Option to fit a MC or MM phono module OR plug in DAC option
- 6 line inputs or 5 plus optional phono card, 2 main out (RCA) and 1 tape output
- High quality relays used for input source selection
- Full remote control of input selector, volume and mute
- Audio output stages utilising discrete transistor class A output buffer
- High quality all aluminium case work
- Remote control
- Three year guarantee
- Available in black or titanium

