

TOTEM 

Discover yours



KIN SUB 10

The **KIN SUB 10** is yet another audio solution in the award winning, versatile KIN family. Compact but packing a big punch, it has the inputs required for a wired connection but can be conveniently **paired wirelessly** with the optional transmitter. However connected and with whatever material, **KIN SUB 10** adds substantial bass and excitement to every listening session.

www.totemacoustic.com



Specifications / Features

The **customized 10" woven fiberglass woofer** is powered by a 300W amplifier, designed in tandem to ensure they harmonize perfectly and produce thunderous and musical bass.

Variable volume, phase, and cross-over controls tailor its output to the environment, speakers, and personal tastes. A unique BASS EQ offers two settings; Natural is pure and linear, providing tight, musical bass. High Impact increases the lower range output by several dB for more intense bass energy.

The **optional LINK Wireless Transmitter** can be added to KIN Play, KIN Play Mini, KIN Amp, or any other system with a subwoofer output to enjoy the same wireless convenience.

Stereo inputs and LFE provide standard connection options, and it pairs wirelessly with the **KIN PLAY Sound Bar without requiring the LINK.**

KIN is all about blending convenience and simplicity with performance and modern technology.

About Totem Acoustic

Created in 1987, Totem's mission is to develop loudspeakers capable of reproducing a truly involving performance. Our goal is to provide designs that are affordable, cosmetically timeless, and invoke an emotional response. Music, movies, TV, and video games are accurately rendered with a powerful focus that is yet soul stirring.

Design: Powered Subwoofer

Enclosure: Sealed

Amplifier: Class D 300 watts

Woofer: 10" cone composed of high tensile spun fiberglass stands top coated and bonded to a cellulosic core. Driven by vented magnetics utilizing an oversized ferrite magnet assembly. Butyl rubber surround.

Voice Coil: High temperature enamel resin coated copper wire wound on a vented aluminum former.

Frequency Response: 27Hz - 200 Hz

Cross Over: Variable - 50Hz to 150Hz -24dB

Phase: Variable - 0 to 180 degrees variable

Inputs: Stereo RCA/LFE/Wireless

Power Modes: Auto/On

Dimensions (HxWxD): 330 x 292 x 345 mm /
13 x 11.5 x 13.5"

Accessories: Magnetic Grill, Adhesive Feet & Power Cord

Available Finishes: Black and White